




MODEL		P550
Standby Power (50HZ)		440KW/550KVA
Prime Power (50HZ)		400KW/500KVA
Open type	3700*1150*2150mm/3800 kg	
Soundproof Type	4500*1800*2200 mm/5300 kg	
20ft container type	6058*2438*2591mm/6800 kg	
Fuel tank 1000L (8 hours)		
Features <ul style="list-style-type: none">• Compact structure with high-strength chassis;• Easy operation and maintenance, Low cost;• Excellent performance damping system;• Compliance with international electrical safety standards of electrical system;• High-performance maintenance-free batteries with isolation switch• 50 Radiator;• Top lifting, Forklift bottom hole design, easy to transport;• Absorber;• Convenient power output interface;• Customized design for user;• Ripple flex exhaust pipe, exhaust siphon, flange, Industrial muffler;• Dry type air filter, fuel filter, oil filter.		
Genset Technical Data		
Rated voltage	400 V	
Phase	3	
Noise	@ 7m 70dB	
Fuel consumption of 100% load	106 Litres/h	
Fuel consumption of 75% load	81 Litres/h	
Voltage regulation rate	≤±1%	
Random voltage variation	≤±1%	
Frequency regulation rate	≤±5%	
Random frequency variation	≤±0.5%	
Engine Specifications		
Engine model	2506C-E15TAG2	
Engine manufacturer	PERKINS	
Number of cylinders	6	
Cylinder arrangement	Vertical in-line	
Cycle	Four stroke	
Aspiration	Turbocharged, air-air charge cooled	
Bore Stroke (mm mm)	137 x 171	
Displacement (Liter)	15	
Compression Ratio	16.0:1	
Prime power/speed	435KW / 1500rpm	
Standby power/speed	478KW / 1500rpm	
Speed governor	Electrical	
Cooling system	Forced Water Cooling Cycle	
Steady speed droop (%)	≤1%	
Total lubrication system capacity (L)	62	
Coolant capacity (L)	58	
Fuel consumption at 100% load	211(g/kWh) (at 1500RPM)	
Starter motor	DC 24V	
Alternator	DC 24V	
Alternator Specifications :- GP/STAMFORD/LEROY SOMER		
Model	C5D	
Prime power/speed	400KW	
Standby power/speed	440KW	
Connecting Type	3 Phase and 4 Wires, "Y" type connecting	
Efficiency (%)	94,4%	
Rated speed	1500 RPM	
Rated frequency	50 Hz	
Phase	3	
Rated voltage	400 V	
Exciter type	Self excitation, Brushless	
Power factor	0,8	
Voltage adjust range	≥5%	
Voltage regulation NL-FL	≤±1%	
Insulation grade	H	
Protection grade	IP23	

Optional	
Fuel System	
• 12 / 24 hour base tank (single wall)	
• Dual wall base fuel tank	
• Outside fuel tank	
• Automatic fuel feeding	
• Fuel level indicate	
Canopy	
• Hired type	
• Economy Oil heater	
• Trailer	
	
DSE Control Panel	
<p>DSE7320 is an advanced control module based on micro-processor, It is an Auto Mains (Utility) Failure Control Module(AMF), have been designed to start and stop generating sets that include electronic And non-electronic engines. Include the additional capability of being able to monitor a mains (utility) supply. when main is not available, It can automatically start the engine and close generating sets breaker automatically, Accurately measure various operational parameters and display all values and alarms information on the LCD. In additional, it can automatically open breaker, and shutdown the engine after the main supply recovers.</p>	
The control module display <ul style="list-style-type: none">• Generator voltage• Generator frequency• Battery voltage• Engine speed• Load current• Generator KVA, KW, PF• Engine run-time Hours• Engine oil pressure• Engine coolant temperature• Real time clock for time and date, overall runtime	Main Features <ul style="list-style-type: none">• AMF and ATS and communication and expansion function• Designed to work with electronic or non-electronic or gas engine simultaneously. (support many kinds of engines ECU).• Manual, Automatic, Test and remote control mode selectable.• Monitoring and measuring operational parameters of the mains supply and genset.• Indicating operation status, fault conditions, all parameters and alarms• Multiple protections and multiple parameters display.• Includes 12 inputs and eight outputs. 8 inputs are configurable and 4 outputs are configurable.• Can be programmed using the front panel or by using the PC software.• Support twelve languages. The language was edited by customer.• Graded protection: pre-alarm, shutdown and electrical trip, flexible setting.• The module can be pre-set for four operating modes and protecting parameters.• Add DSE860 or DSE865 module, internet network monitoring can be realized.• The firmware can be updated automatically, so customer can have the latest version.